



SILVERLINK 600

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Gas Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and an easy to clean surface, while there's also piezo ignition for easy lighting of the burners. The griddle features two separately controlled heat zones, which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. The griddle, perfect for cafes, pubs and restaurants, is also thermostatically controlled to give accurate temperatures during the cooking process for consistent results.

PRODUCT OPTIONS AND ACCESSORIES

- SB7 750 GRIDDLE SPLASHB
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm

PRODUCT FEATURES

- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- Front mounted control for easy of use during cooking
- Piezo ignition for easy lighting of the burners
- Flame failure device for maximum safety

WEIGHTS & DIMENSIONS

Width	750 mil
Depth	650 mil
Height	415 mil
Weight	54 kg

SHIPPING DETAILS

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	59.4 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	8 kW	Gas Inlet Pressure Required	25 mBar
Electrical Connection Type	Not Applicable	Gas Total BTUs	27296 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	0.57 m ³
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	8 kW, 25600 BTU per hour
Gas Type	Propane	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Mechanical	Number of Burners	2
Cooking Area Plate Depth	405 mm	Number Of Controls	2
Cooking Area Plate Width	712 mm	Number of Heating Zones	2
Cooking Plate Finish Material Type	Polished Steel	Plate Shape	Rectangle
Food Production Rate	190 x 115g [4oz] burgers [frozen] per hour	Plate Thickness	12 mm
Legs or Casters	Not Applicable	Temperature Maximum	250 °C
Lower Platen Surface Type (multi-select)	Smooth	Temperature Minimum	50 °C
		Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

