

1N0FT2G



GAS GRIDDLE WITH RIBBED MILD STEEL PLATE



Available only for countries outside the European Community. Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Satin finished Fe510D steel cooking plate. Delivered with: plate plug. Heating by two independent burner groups controlled by modulating thermostat valve. Working temperature (min-max): 120-320°C.



<i>Plate</i>	Fe510D - ribbed	<i>Power supply</i>	Gas
<i>Worktop thickness</i>	2 mm		

Functional features

- Ribbed cooking plate made in special Fe510D steel thickness 15 mm.
- Plate sealed and slightly recessed into the worktop, obtained by a special mould (Hygienic Design patented), satin-finished.
- Working temperature (min-max): 120-320°C.
- Cooking plate surface 715x635 mm.
- Specific output per useful surface dm² 445 W.
- n. 2 independent cooking areas power rated at 10.5 kW each
- Installations through suitable accessories: on under compartment, counter solution on feet, bridge solution, cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Combustion chambers separated for each burner to optimize both the yield and the gas consumption.
- Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1.75 lt.
- Electronic spark ignition, manual ignition allowed.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Rubber protection under the knobs against water infiltration.
- Sealed flue on the top.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Available only for countries outside the European Community.
- Security control on gas operation ensured by thermostatic valve, pilot light and thermocouple.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

<i>Working voltage</i>	230V 1N~ / 50 ÷ 60Hz	<i>Net Weight</i>	85 kg
<i>Gross Weight</i>	90 kg	<i>Electric Power</i>	0,001 kW
<i>Gas Power</i>	21 kW	<i>Dimensions</i>	80x92x25 cm
<i>Packing</i>	102x87x68 cm		

GAS GRIDDLE WITH RIBBED MILD STEEL PLATE
Icon9000 prof.900 - 2 mm

