

LINCAT SILVERLINK PROPANE GAS COUNTER-TOP GRIDDLE -STEEL PLATE - W 450 MM - 5.5 KW

MODEL: GS4/P



Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Gas Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and an easy to clean surface, while the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results. The griddle, perfect for cafes, pubs and restaurants, comes with piezo ignition for easy lighting of the burners.

PRODUCT OPTIONS AND ACCESSORIES

- SB4 450 GRIDDLE SPLASHB
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand for units W 450 mm

PRODUCT FEATURES

- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- · Front mounted control for easy of use during cooking
- Piezo ignition for easy lighting of the burners
- Flame failure device for maximum safety







LINCAT SILVERLINK PROPANE GAS COUNTER-TOP GRIDDLE -**STEEL PLATE - W 450 MM - 5.5 KW**

MODEL: GS4/P

| WEIGHTS & DIMENSIONS | |
|----------------------|---------|
| Width | 450 mil |
| Depth | 650 mil |
| Height | 415 mil |
| Weight | 35.1 kg |

| SHIPPING DETAILS | |
|----------------------------|-------------------------|
| Ship Width | 70 cm |
| Ship Depth | 55 cm |
| Ship Height | 63.5 cm |
| Ship Weight | 38.61 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



| ENERGY SPECS | | | |
|----------------------------|----------------|-------------------------------------|-----------------------|
| Primary Energy Source Type | Gas | Gas Inlet Size | 0.5 in |
| Kilowatts | 5.5 kW | Gas Inlet Pressure Required | 25 mBar |
| Electrical Connection Type | Not Applicable | Gas Total BTUs | 18766 BTU |
| Electrical Plug Type | Not Applicable | Gas Consumption at Max Use Per Hour | 0.39 m ³ |
| Number of Electrical Plugs | Not Applicable | Total Heat Input at Max Use | 5.5 kW, 16700 BTU per |
| Gas Type | Propane | | hour |
| | • | Energy Saving | No |

| ADDITIONAL SPECIFICATIONS | | | |
|--|----------------|-----------------------------|-------------------|
| Control Type | Mechanical | Number of Burners | 2 |
| Cooking Area Plate Depth | 405 mm | Number Of Controls | 2 |
| Cooking Area Plate Width | 412 mm | Number of Heating Zones | 2 |
| Cooking Plate Finish Material Type | Polished Steel | Plate Shape | Rectangle |
| Legs or Casters | Not Applicable | Plate Thickness | 12 mm |
| Lower Platen Surface Type (multi-select) | Smooth | Thermostat Element Location | Under Plate Mount |

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024










MODEL: GS4/P

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024