



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SB9 900 GRIDDLE SPLASHBACK - GS9 ONLY
- SLS9 Lincat Silverlink 600 Free-standing Floor Stand - for units W 900 mm
- HCL9 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 900 mm - 1.0 kW

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and an easy to clean surface, and also features two separately controlled heat zones, which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. The two-zone system is designed to give you maximum flexibility during service. The griddle, perfect for cafes, pubs and restaurants, is also thermostatically controlled to give accurate temperatures during the cooking process for consistent results.

PRODUCT FEATURES

- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- 2 cooking zone to give maximum flexibility during service
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Front mounted control for easy of use during cooking

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	900 mil
Depth	620 mil
Height	330 mil
Weight	60.9 kg

SHIPPING DETAILS

Ship Width	101.5 cm
Ship Depth	72 cm
Ship Height	59.5 cm
Ship Weight	66.99 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	Single Phase 37.4/Three Phase L1=12.1; L2=12.1; L3=13.1	Electrical Connection Type	Direct Hardwired
Electrical Voltage	230 volts/400 volts	Electrical Plug Type	Hardwired
Electrical Watts	8600	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single, Three	Dedicated Circuit Required	Yes
Kilowatts	8.6 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob	Number Of Controls	2
Cooking Area Plate Depth	405 mm	Number of Heating Zones	2
Cooking Area Plate Width	862 mm	Plate Shape	Rectangle
Cooking Plate Finish Material Type	Polished Steel	Plate Thickness	12 mm
Food Production Rate	290 x 115g [4oz] burgers [frozen] per hour	Temperature Maximum	250 °C
Legs or Casters	Not Applicable	Temperature Minimum	50 °C
Lower Platen Surface Type (multi-select)	Smooth	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

