



SILVERLINK 600

Not only does the Silverlink 600 Electric Pasta Boiler deliver perfect pasta every time, it also has the versatility to be used as a steamer and Bain Marie, too. The boiler comes with a lid to reduce heat up time and also cover the tanks when not in use, while the thermostatic control maintains an accurate water temperature throughout. Ideal for cafes as well as smaller pubs and restaurants, the boiler also features enhanced resistance to punishing salt and starch corrosion with high quality grade 304 stainless steel tanks, basket support plates, and corrosion-resistant elements.

A/A FILE NUMBER:

PRODUCT OPTIONS AND ACCESSORIES

- BA114 BASKET 1/2 PASTA
- BA116 BASKET L/H 1/4 PASTA
- BA112 BASKET PASTA
- BA115 BASKET R/H 1/4 PASTA
- CC3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 300 mm
- CN3 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 300 mm
- SLS3 Lincat Silverlink 600 Free-standing Floor Stand - for units W 300 mm
- HC3 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 300 mm - 0.25 kW
- HCL3 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 300 mm - 0.25 kW

PRODUCT FEATURES

- Delivering perfect pasta, time after time
- Front mounted controls ensure safe working practice
- Hinging element with safety cut-out provides easy access to tank for cleaning
- Thermostatic control maintains accurate water temperature
- Enhanced resistance to punishing salt and starch corrosion with high quality grade 304 stainless steel tanks, basket support plates, and corrosion-resistant elements
- Front drain taps with straight drain pipes for fast, easy drainage of water - and no blockages
- Lid to reduce heat up time and also cover tanks when not in use

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	300 mil
Depth	600 mil
Height	330 mil
Weight	12.5 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	40 cm
Ship Height	49.5 cm
Ship Weight	13.75 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	13	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	3000	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	3 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Capacity Volume	11 l
Control Type	Mechanical
Food Production Rate	5kg pasta - penne [fresh] per hour
Mixing Valve	No
Number of Baskets	0
Number of Vats (batteries)	1
Overflow Prevention	No
Water Fill	Manual

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

