
GASTRONOME UPRIGHT CHILLER


- Blower System
- Magnetic Solid Door

BS 2FDUC/G/GN 2 Door

1350mm










125mm

Front View



BS 3FDUC/G/GN 3 Door





HIGHLIGHTS

High-density Cyclo-isopentane Polyurethance

insulated body saves energy.

Automatic defrost system

saves energy consumption and provide shortest possible defrost cycle.

Refrigeration sytem protected from corrosion

by urethane-treated evaporator coil.

Blower system (assisted with fan)

will ensure homogenous coolness in the storage space.

Magnetic and robust stainless steel door.

Offer a higher tensile strength, which means fewer dents and scratches.

Environmentally friendly refrigerant

(CFC and HCFC Free) R134a.

Effective counter - balanced weight system self closing door provides smooth, even, positive closure.

127 ~ 152mm adjustable stainless steel legs or 100mm castor wheel.

4 tier removable and adjustable shelves.

Self contained system

no plumbing required.

Tested at ambient temperature of 38°C,

with no load.

TABLE INFO







	1 DOOR	2 DOOR	3 DOOR
MODEL	BS 1FDUC/G/GN	BS 2FDUC/G/GN	BS 3FDUC/G/GN
Temperature°C (celsius)	+2 to +8	+2 to +8	+2 to +8
External Dimension (mm)	675 x 830 x 2060	1350 x 830 x 2060	2020 x 830 x 2060
Internal Dimension (mm)	555 x 720 x 1460	1225 x 720 x 1460	1890 x 720 x 1460
Gross Volume (Litres)	580	1285	1980
Voltage/ Frequency (V/ Hz)	230V/50Hz	230V/50Hz	230V/50Hz
Weight (kgs)	130	180	250
Compressor	1/3	1/2	3/4
Wattage (W)	418 - 462	456 - 504	803 - 887
Ampere (A)	2.8 - 3.2	3.1 - 3.5	5.4 - 6.0
Energy Consumption (kw/ 24h)	12.4 - 13.6	13.9 - 15.3	16.1 - 17.7
Refrigerant/ Grams	R134a / 380g	R134a / 380g	R134a / 380g
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
Temperature Control	Digital	Digital	Digital
Shelves (Pvc)	5	10	15
Unit For 20ft Container	20	10	6
Unit For 40ft Container	43	22	13

Standard product can be supplied with either

- 1. Shelving / Foodpan
- 2. Castor Wheel / Bullet Feet

As product improvement is an on going process, we reserve the right to change specifications or design without notice.