

1S0FT1E



ELECTRIC GRIDDLE WITH SMOOTH MILD STEEL PLATE



Available only for countries outside the European Community. Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Satin finished Fe510D steel cooking plate. EVEN-PRO SYSTEM. Delivered with: plate plug. Heating by two independent heating elements made in AISI 309 stainless steel placed under the plate, safety thermostat. Working temperature (min-max): 70-260°C.



<i>Plate</i>	Fe510D - smooth	<i>Power supply</i>	Electricity
<i>Product fitting up</i>	Counter Top	<i>Worktop thickness</i>	2 mm

Functional features

- Smooth cooking plate made in special Fe510D steel thickness 12 mm.
- Plate with satin-finish, recessed into the worktop; welded around the perimeter and sealed.
- Operating temperature: 70-260°C.
- Dimensions of the cooking plate (W x D): 730 x 530 mm. Frontal simmering zone 50 mm.
- n. 2 independent cooking areas power rated at 5.1 kW each
- EVEN-PRO Ensures high cooking uniformity and temperature stability. The cooking heating elements are integrated with a 5 mm aluminum diffuser ensuring quick temperature rise, high efficiency in the heat transfer, temperature stability and energy efficiency.
- EASY-WASH: this is the program to clean the cooking plate bringing the surface temperature up to 75°C, in order to wash it reducing water and detergent.
- Commutable to 230V3 50/60 Hz
- Two groups of three + three armoured heating elements made of in AISI 309 stainless steel, each heating a half plate.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Fett drain outlet diameter 32 mm with removable heat-resistant food-grade plastic plug.
- Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1.5 lt.
- Metal ergonomic knobs with rubber protection against water infiltration.
- RADIUS rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

Safety equipment and approvals

- Safety thermostat protecting the appliance and electric parts.
- Max temperature safety thermostat.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

Optional

- Splash guards, cleaning plate scraper and blades; pipe for the water discharge during the cleaning of the plate.

Technical Data

<i>Working voltage</i>	400V 3N~ / 230V 3~ / 50-60 Hz	<i>Electric Power</i>	10,2 kW
<i>Dimensions</i>	80x72x25 cm	<i>Packing</i>	86x82x65 cm

ELECTRIC GRIDDLE WITH SMOOTH MILD STEEL PLATE

Icon7000 prof.700

