

Hood Type Touch Panel Dishwashers



- User friendly Touch Control Panel.
- Stainless steel body, washing and boiler tank. Contains stainless steel tank filter.
- Monoblock washing tank with round corners - Hygienic.
- 2.8 l water consumption per cycle.
- Adjustable detergent / rinse aid time from touch panel.
- Digital pressure switch for washing tank.
- Easy to follow washing steps with dynamic and coloured touch screen.
- Suitable for corner or in-line installation.
- Washing arms both available in stainless steel and reinforced polypropylene.
- Adjustable feet for height optimization.
- Easy start up: single button for water filling and heating in the boiler tank.
- Electrical components and wiring according to international standards and security regulations.
- Digital controlled, washing and rinsing temperatures for efficient washing.
- Non-return - Check valve system.
- Digital screen for temperature and error displays.
- Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C).
- Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C).
- Gentlewash option , Adjustment of washing pressure level with the minimum wear to dishes.
- The soft start option enables ultra-sensitive and quiet starting of the program.

| | HOOD TYPE DISHWASHER CODE | | | | | | |
|--------------------------------------------------|---------------------------|---------------|---------------|---------------|----------------|---------------|---------------|
| | OBM 1080T P | OBM 1080T PD | OBM 1080T PDT | OBM 1080T PDR | OBM 1080T PDRT | OBM 1080T R | OBM 1080T RT |
| | 071T.10000.BB | 071T.11000.BB | 071T.11010.BB | 071T.11100.BB | 071T.11110.BB | 071T.00100.BB | 071T.00110.BB |
| Rinse Aid Dispenser | ✓ | ✓ | ✓ | ✓ | ✓ | - | - |
| Detergent Dispenser | - | ✓ | ✓ | ✓ | ✓ | - | - |
| Rinsing Pump | - | - | - | ✓ | ✓ | ✓ | ✓ |
| Drain Pump | - | - | ✓ | - | ✓ | - | ✓ |
| 3 Baskets Promotional (Plate, Glass and Cutlery) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Stainless Steel Washing Arms | OPT | OPT | OPT | OPT | OPT | OPT | OPT |
| Soft Start | OPT | OPT | OPT | OPT | OPT | OPT | OPT |
| Gentlewash | OPT | OPT | OPT | OPT | OPT | OPT | OPT |

For the models do not have rinsing pump, program times are 5 seconds longer.

| TECHNICAL FEATURES | | | |
|--------------------------------|----------------------------|----------------------------------|-----------------------------------------------------------------------------------|
| Electric connection | 400V 3NPE / 50 Hz | Rinsing pump power | 0,25 kW (OBM 1080T PDR / OBM 1080T PDRT / OBM 1080T R / OBM 1080T RT) |
| Total rating | 9.66 kW | Water inlet pressure / Temp. | 2-4 Bar / 50 °C |
| Washing capacity (plate/hr) | 1152 plate (Max.) | Heat power (Washing/Rinsing) | 2 / 9 kW |
| Washing capacity (basket/hr) | 72 / 36 / 27 / 24 / 18 | Dirty water discharge connection | 1 1/4" (Ø42 mm) without drain pump models 3/4" (Ø28 mm) with drain pump models |
| Washing / Boiler tank capacity | 23 / 7 l. | Maximum noise | 75 dBA |
| Washing program number | 5 | Gross weight | 120 (±5) kg |
| Program times (seconds) | 50 / 100 / 130 / 150 / 190 | Dimensions (WxDxH) | 700x785x1480 (1960) mm |
| Washing water temp. | 55-60°C | Protection class | IPX5 |
| Rinsing water temp. | 80-85 °C (max.) | Rack dimension | 50 x 50 cm |
| Water inlet connection | 3/4 " | Useful loading height | 445 mm |
| Washing pump power | 0.66 kW | Inclination | 6° |